



# DEARSAN

SHIPYARD



## GENERAL

• Class Notation : RINA I + HULL+MACH. UNRESTRICTED NAVIGATION, ATU-UMS, ESCORT TUG, FiFi1

### TYPE

Bollard Pull  
Length (LOA)  
Beam (B)  
Draft (T) (Excluding Skeg)  
Displacement (Full Load)  
Max. Speed  
Complement

### RAmparts 3200

65-70 T  
32,0 m  
11,6 m  
4,3 m  
900 t  
13,0 Knt.  
8-10 persons

### RAstar 3400

80 T  
34,0 m  
13,5 m  
4,75 m  
1180 t  
12,0 Knt.  
8-10 persons

### PROPULSION

Main Engine  
Propulsion  
Main Generator  
Harbour Generator

2 x 2040 KW Diesel Engine  
2 x CPP ASD  
2 x 175 KW Diesel Gen.  
1 x 60 KW Diesel Gen.

2 x 2650 KW Diesel Engine  
2 x CPP ASD  
3 x 190 KW Diesel Gen.  
1 x 80 KW Diesel Gen.

### DECK MACHINERY

Deck Crane  
Boat with Davit  
Hydraulic Towing Winch  
Hydraulic Hawser Winch

Foldable, Lifting Moment 14,6 tm.  
GRP Rescue Boat, 6 person  
1000 m. of 52 mm. steel wire  
2 x 150 m. of 60 mm. Drum capacity.

Foldable, Lifting Moment 31,5 tm.  
GRP Rescue Boat, 6 person  
1000 m. of 56 mm. steel wire  
2 x 200 m. of 680 mm. Drum capacity.

### CAPACITIES

Fuel  
Fresh Water  
Foam  
Fire Fighting

170 t.  
4000 l.  
17400 l.  
1200 m3/h water, 300 m3/h foam

170 t.  
4000 l.  
17400 l.  
1200 m3/h water, 300 m3/h foam

### NAVIGATION SYSTEMS

- 2 x X-Band Navigation Radar
- ECDIS
- DGPS
- Auto Pilot
- Gyro , Magnetic Compass
- Echo Sounder,
- Speed Log
- AIS
- Wind Speed and Direction

### COMMUNICATIONS

- VHF Transceiver
- MF/HF Transceiver
- VHF DSC Radio
- Inmarsat C
- Telephone System
- Public Address System
- Intercom System
- GMDSS A3 (EPIRB+SART+ NAVTEX)

